

# Total Power Box Solutions, Inc.

Product datasheet

## Thermoplastic Lighting Panelboard

Thermoplastic - Panelboards

Flush-mounted lighting panelboard in a self-extinguishing, heat-resistant thermoplastic frame and cover, with a 1.0 mm galvanized steel enclosure and an insulated comb copper bus rated at 125 A max. Available with transparent or opaque covers.

### KEY SPECIFICATIONS

DEGREE OF PROTECTION

**IP40**

RATED VOLTAGE

**230/400 VAC**

RATED CURRENT

**Up to 125 A**

COLOR

**Milky white**

### FULL SPECIFICATIONS

#### ELECTRICAL

|                           |                                         |   |
|---------------------------|-----------------------------------------|---|
| Degree of protection      | <b>IP40</b>                             | - |
| Rated current             | <b>Up to 125 A</b>                      | - |
| Rated operational voltage | <b>230/400 VAC</b>                      | - |
| System compatibility      | <b>1 phase + N + G, 3 phase + N + G</b> | - |

#### CONSTRUCTION

|               |                                                             |   |
|---------------|-------------------------------------------------------------|---|
| Mounting type | <b>Flush mounted</b>                                        | - |
| Frame & cover | <b>Thermoplastic, self-extinguishing and heat resistant</b> | - |
| Enclosure     | <b>Galvanized steel, 1.0 mm thick</b>                       | - |
| Busbar        | <b>Insulated comb copper bus, rated 125 A max.</b>          | - |
| Color         | <b>Milky white</b>                                          | - |
| Cover options | <b>Transparent or opaque</b>                                | - |